

Technical Data Sheet Neues Zuhause

Order processing:

G+J Corporate Editors GmbH
 Anna-Ulrike Soldat
 P.O. Box 11
 20444 Hamburg, Germany
 Tel.: (+49-40) 40-3703-5304
 Fax: (+49-40) 40-3703-5302
 E-Mail: soldat.anna-ulrike@guj.de

Delivery address for printing materials:

Prinovis Itzehoe GmbH & Co. KG
 Jürgen Stimming
 Am Vossberg
 25524 Itzehoe, Germany
 Phone: (+49-4821) 777-369
 Fax: (+49-4821) 777-369
 E-Mail: bh-anzeigen.itzehoe@prinovis.com



Data format



Adobe-PDF X/3 status 2002

Modus: CMYK

Fonts must be imbedded. Negative fonts should be at least 8 point; fine serifs should be avoided. Multiple-Master fonts and Doppelbyte fonts may not be used. Doppelbyte True Type fonts should not be used, and if used must be approved in advance. Please do not use any typeface modifications such as bold or italics.

Images must be embedded. The image resolution should be 304 dpi (in relation to the final format of the image), Bitmaps need a resolution of 1200 dpi, for CT 304 dpi. The quality of the JPEG compressed images must be defined by the deliverer. Embedded ICC-profiles will not be evaluated.

Digital data transfer

Delivery printing material:

Technical specifications: Current and binding specifications can be found at www.duon-portal.de

Profile



Position: Inner pages, rotogravure according to the PSR process standard rotogravure
 Profile: PSRgravureLWC, Paper class LWC

Position: Cover, offset according to ISO 12647-2
 Profile: ISO Coated v2 300% (ECI), paper category: paper class 1 and 2, glossy or matte coated illustration print paper.

Production

Position: Inner pages: rotogravure according to the PSR process standard rotogravure.

Weight 4c: pos. 0.25 mm - neg. 0.35 mm.

Weight b/w: pos. 0.25 mm - neg. 0.5 mm.

Area coverage: 340%.

Achromatic colour setup: No UCR/ GCR.

Position: Cover: offset according to ISO 12647-2

Weight 4c: pos. 0.05 mm - neg. 0.05 mm.

Weight b/w: pos. 0.05 mm - neg. 0.05 mm.

Area coverage: 300%.

Binding method: saddle stitch

Trim Size: (wide x height in mm) 215 x 280

Trimming edge: for bleed add 5 mm on all sides

Proofs

Position: Inner pages: rotogravure according to the PSR process standard rotogravure. The proof must be labelled with the name of magazine, the name and issue of the advertisement, and name and telephone number of the data producer. The proof must be produced 1:1 from the digital data supplied and contain the Ugra/Fogra Media Wedge.

Position: Cover: offset according to ISO 12647-2

The proof must be labelled with the name of magazine, the name and issue of the advertisement, and name and telephone number of the data producer. The proof must be produced 1:1 from the digital data supplied and contain the Ugra/Fogra Media Wedge.

Important!

Profile: Data produced in the PSR process standard for rotogravure will be converted to the printing colour space at the printers through a standard conversion. The colour space may not contain UCR/GCR.